

# Village of

Ryan Hutto

Applicant to provide all information in red

Shingles: Architectural  
Fiberglass  
Asphalt

Roof Sheathing  
1/2 X 4 X 8  
OSB  
PLY  
15lb Felt

12  
Pitch

10"

☐ Trusses  
@ 24" OC

For Spans Greater than 6 Feet Use  
Mechanical Clip Fasteners at Plate to  
Rafter/Truss Connection  
\*Span Includes Overhang

Wall Sheathing  
3/8 X 4 X 8

Siding  
LP SmartSide panel siding

No Grade Beam Foundation!  
(entire perimeter)

Anchor Bolts: Max. 18"  
from Corners  
and 6' Apart

Rafter Size 2 X 6  
Rafter Spacing 24 OC  
Collar Tie Size 2 X 4  
Collar Tie Spacing 48 OC  
Joist Size - X -  
Joist Spacing - OC  
Rafter Species/Grade construction  
Joist Species/Grade -  
Ridge - X - Double 5/8" Gussets

Wall Studs 2 X 4  
@ 16 OC

Interior Finish? -  
Insulation? -  
Will Structure Be Heated? -  
Will Electric be Installed? -

Treated Bottom Plate

12

5x1 Trussom  
2X6X63" HDR

Rafter Direction

**Floor Plan**

72x80  
Steel doors  
2X6X78"  
HDR

18

Indicate the Following on Floor Plan Above:

- 1) Dimension (L X W)
- 2) Location & Size of Windows & Doors
- 3) Joists, Truss and /or Rafter Direction
- 4) Length & Size of all Headers
  - a) At Service Door
  - b) At Overhead Door
  - c) At Windows

Height of Building  
From Grade to Peak \_\_\_\_\_

Min. 4" Concrete Reinforced with  
6 X 6 X #10 Woven Wire Mesh over  
Min 4" Compacted Granular Fill

**Accessory Structure Wall Section**