

**GENERAL NOTES**

- COORDINATE LIGHT FIXTURE LOCATIONS IN MECHANICAL EQUIPMENT ROOMS WITH OTHER CONTRACTORS PRIOR TO ROUGH IN.
- DEVICE LOCATIONS MAY BE DISTORTED FOR CLARITY. LOCATE DEVICES SYMMETRICALLY WITH THE ARCHITECTURAL ELEMENTS.
- CONTROL EXTERIOR LIGHTING VIA TIME CLOCK AND PHOTOCELL FOR DUSK TO DAWN CONTROL.
- DEVICE LOCATIONS MAY BE DISTORTED FOR CLARITY. LOCATE DEVICES SYMMETRICALLY WITH THE ARCHITECTURAL ELEMENTS.
- SEE LIGHTING FIXTURE LEGEND FOR FIXTURE WIRING INFORMATION.

**KEYNOTES**

- COORDINATE MOUNTING HEIGHT WITH OWNER.
- THE BOTTOM OF THE SIGN SHALL BE NOT LESS THAN 10 INCHES NO MORE THAN 18 INCHES ABOVE THE FLOOR LEVEL. THE SIGN SHALL BE FLUSH MOUNTED TO THE DOOR OR WALL. WHERE MOUNTED ON THE WALL, THE EDGE OF THE SIGN SHALL BE WITHIN 4 INCHES OF THE DOOR FRAME ON THE LATCH SIDE.

**PROJECT INFORMATION**

PROPOSED BUILDING FOR:  
**HOME 2 SUITES**  
 1212 S. 70TH STREET • WEST ALLIS, WI 53214

PROFESSIONAL SEAL

**SHEET DATES**

SHEET ISSUE MAY 3, 2022

REVISIONS

**JOB NUMBER**

2175400

**SHEET NUMBER**

**E2.1L**



**FIRST FLOOR PLAN - LIGHTING**  
 SCALE: 1/8" = 1'-0"  
 NORTH

C:\Users\james\Documents\2175400\_E2.1L.dwg, 5/3/2022 4:55:38 PM